



ST-54

ST-54 double lance

The R+M ST-54 double lance can work with pressures up to 310 bar. The double lance is a special washing lance made up of two parallel tubes. By moving the knob it is possible to open or close one of the two outputs while the other remains always open. In the always open outlet the high pressure nozzle is normally mounted, while in the other outlet we find the low pressure nozzle. When both outlets are open the system works in low pressure, allowing the Venturi injector mounted upstream to suck the chemical product. By closing the low pressure outlet, the ST-54 works like a normal high pressure wash lance. This type of lance is normally used with pressure washers designed to supply water and chemical product.

FIELDS OF APPLICATION



High
pressure
washer



Municipality



Food
industry

TECHNICAL DATA

Max pressure (bar)	310
Max flow rate (l/min)	40
Outlet	2 x 1/4" Npt F

EMILTEC Srl a socio unico

Sede Legale e Amministrativa: Via Carlo Boetti, 8/B • 42124 Reggio nell'Emilia • Italy

Tel +39.0522.941825 • Fax +39.0522.1601370 • C.F. e P.IVA 02674440355

www.emiltec.com info@emiltec.com



PART NUMBERS

PN	MAX PRESSURE (BAR)	LENGTH (MM)	INLET	TUBE	JIT DELIVERY
216200054600	310	980	G 1/4" M	2x 1/4" sst	✓
216200054630	310	980	KEW style quick coupling	2x 1/4" sst	✓
21651760	310	980	G 1/4" M	2x 1/4" zinc-plated	
216516605	310	980	KEW style quick coupling	2x 1/4" zinc-plated	

MORE INFORMATION

- Brand: R+M
- Equipped with nozzle holders
- Made in Germany

EMILTEC Srl a socio unico

Sede Legale e Amministrativa: Via Carlo Boetti, 8/B • 42124 Reggio nell'Emilia • Italy

Tel +39.0522.941825 • Fax +39.0522.1601370 • C.F. e P.IVA 02674440355

www.emiltec.com info@emiltec.com

